Ordering Instructions

60 X XXXX X - X XX - XX - XX

60 — 60 Series High Security Cam Lock

X — Cylinder Type
- - = Original
- W = Biaxial
- T = Medeco²

XXXX — Model Number
- 0250 = 5 pin, 11/16" length
- 0350 = 5 pin, 7/8" length
- 0450 = 5 pin, 1" length
- 0550 = 4 pin, 7/8" length
- 0650 = 5 pin, 1 1/8" length
- 0750 = 4 pin, 11/16" length
- 0850 = 4 pin, 5/8" length
- 0950 = 5 pin, 3/4" length
- 1150 = 5 pin, 5/8" length
- 1251 = 3 pin, 5/8" length
- 1250 = 3 pin, 7/16" length
- 1450 = 5 pin, 1 1/2" length
- 1452 = 5 pin, 2" length

X — Plug Head Thickness
- T = Thick head plug

X — Mounting Flats
- 1 = Single D (1 flat)
- 2 = Double D (2 flats)

XX — Rotation and Keypull
- 19 = 90° Clockwise, 1 keypull
- 29 = 90° Clockwise, 2 keypull
- 39 = 90° Counterclockwise, 1 keypull
- 49 = 90° Counterclockwise, 2 keypull
- 59 = 180° Clockwise, 1 keypull
- 69 = 180° Clockwise, 2 keypull
- 79 = 180° Counterclockwise, 1 keypull
- 89 = 180° Counterclockwise, 2 keypull

XX — Finish
- (26) Satin Chrome Standard

XX — Key Selection
- (Assigned by Medeco Customer Service)

XX — Operation Code